



## E/R 12 Slick Rope

Manufactured with Ultra High Molecular Weight Polyethylene fiber, this rope offers high strength, low stretch, and is easy to splice. Fiber is 2.5x stronger than conventional pulling ropes with a 25% friction coefficient reduction. Stock with factory-spliced pulling eyes at each end.



### E/R 12 Slick Rope

Part Number	Nominal Diameter (in.)	Length (ft.)	Tensile Strength (lbs.)	Elongation at Break (%)	Specific Gravity	Approximate Package Weight (lbs.)
ER12040300	1/8	300	1,125	3.5	0.96	2.5
ER12080300	1/4	300	7,600	3.5	0.96	3.5
ER12080600	1/4	600	7,600	3.5	0.96	7
ER12081200	1/4	1200	7,600	3.5	0.96	100
ER12180300	9/16	300	40,476	3.5	0.96	26
ER12180600	9/16	600	40,476	3.5	0.96	52
ER12180900	9/16	900	40,476	3.5	0.96	77
ER12181200	9/16	1200	40,476	3.5	0.96	103
ER12182000	9/16	2000	40,476	3.5	0.96	172
ER12182500	9/16	2500	40,476	3.5	0.96	215
ER12240300	3/4	300	83,000	3.5	0.96	54.5
ER12240600	3/4	600	83,000	3.5	0.96	109
ER12241200	3/4	1200	83,000	3.5	0.96	218
ER12241500	3/4	1500	83,000	3.5	0.96	272.5
ER12243000	3/4	3000	83,000	3.5	0.96	545

