



E/R 12 Slick Rope®

Manufactured with Ultra High Molecular Weight Polyethylene fiber, this rope offers high strength, low stretch, and is easy to splice. Fiber is 2.5x stronger than conventional pulling ropes with a 25% friction coefficient reduction. Stock with factory-spliced pulling eyes at each end.
Direct equivalent to Southwire QWIKrope®



E/R 12 Slick Rope

Part Number	Nominal Diameter (in.)	Length (ft.)	Tensile Strength (lbs.)	Elongation at Break (%)	Specific Gravity	Approximate Package Weight (lbs.)
ER12040300	1/8	300	1,125	3.5	0.96	2.5
ER12080300	1/4	300	7,600	3.5	0.96	3.5
ER12080600	1/4	600	7,600	3.5	0.96	7
ER12081200	1/4	1200	7,600	3.5	0.96	100
ER12180300	9/16	300	40,476	3.5	0.96	26
ER12180600	9/16	600	40,476	3.5	0.96	52
ER12180900	9/16	900	40,476	3.5	0.96	77
ER12181200	9/16	1200	40,476	3.5	0.96	103
ER12182000	9/16	2000	40,476	3.5	0.96	172
ER12240300	3/4	300	83,000	3.5	0.96	54.5
ER12240600	3/4	600	83,000	3.5	0.96	109
ER12241200	3/4	1200	83,000	3.5	0.96	218
ER12241500	3/4	1500	83,000	3.5	0.96	272.5
ER12243000	3/4	3000	83,000	3.5	0.96	545

QWIKrope® is a registered trademark of Southwire Company, LLC. Erin Rope is not affiliated with or endorsed by Southwire.



erin rope corporation

2661 West 139th Street • Blue Island, IL 60406 • 708-377-1084 • Fax 708-377-1094
email: sales@erinrope.com • web: www.erinrope.com